





ANTI BLOCK Additive - SM Aba-L

DESCRIPTION:

Resin SM ABA-L (Anti Block Additive-L) is a nonreactive, chemically inert and non-toxic polymer.

SPECIFICATION:

Appearance	Whitish Liquid
% Solid	15 ± 2

SOLVENT COMPOSITION:

Resin	15% ± 2
Solvent	85% ± 2

COMPATIBILITY:

Readily compatible with N.C., Vinyl's, Maleic & Ketonic Resins.

SOLUBILITY:

Esters are the true solvent. Blend of ketones, alcohols, esters & aromatic hydrocarbons (Toluene) can be used. Only Ethyl Acetate can also be used as reducer during printing.

The leaflet provides information based on experience and lab experiments, but values may vary in practical use. Customers should ensure product suitability and not base legal claims on the leaflet.







APPLICATIONS:

Anti Setoff Additive, improves inter colour trapping.

STORAGE:

SM ABA-L should be stored in its sealed original packing at temperature between 25 – 40degC. Under this condition, the product will remain stable for about six months.

The leaflet provides information based on experience and lab experiments, but values may vary in practical use. Customers should ensure product suitability and not base legal claims on the leaflet.

F. +971 (6) 526 3737

info@inksuae.com